

Revision: 2024-07-31

Lujob M Conveyor Lubricant

Version: 02.0

1. IDENTIFICATION

Product name: SDS #: Recommended use:

M\$0801150 • Industrial/Institutional • Conveyor Track Treatment

Lujob M Conveyor Lubricant

Conveyor frack freatment
 This product is intended to be diluted prior to use

Uses other than those identified are not recommended

Canadian Headquarters

Phone: 1-800-668-7171

6150 Kennedy Road Unit 3

Mississauga, Ontario L5T 2J4

Diversey Canada, Inc.

Uses advised against:

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 1300 Altura Rd., Suite 125 Fort Mill, SC 29708 Phone: 1-888-352-2249 SDS Internet Address: https://sds.diversey.com

Emergency telephone number:

1-800-851-7145; 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Serious eye damage, Category 1 Specific target organ toxicity (repeated exposure), Category 2 Skin irritation, Category 2 Corrosive to metals, Category 1



Signal word:

Danger.

Hazard Statements

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE. MAY BE CORROSIVE TO METALS.

Precautionary Statements

Causes burns/ serious damage to mouth, throat and stomach. Keep container tightly closed. Keep only in original container. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Wear chemical-splash goggles and chemical-resistant gloves. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Get medical attention or advice if you feel unwell. Take off contaminated clothing and wash it before reuse. Absorb spillage to prevent material damage. Store in corrosive-resistant container with a resistant inner liner. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION:. DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Mix only with water. Can react to release hazardous gases. May vigorously react with strong alkaline products resulting in spattering and excessive heat.

<u>Health hazards not otherwise classified (HHNOC)</u> - Not applicable <u>Physical hazards not otherwise classified (PHNOC)</u> - Not applicable

Classification for the diluted product 1:50

This product, when diluted as stated on the label, is not classified as hazardous according to OSHA 29CFR 1910.1200 (HazCom 2012-GHS) and Canadian Hazardous Products Regulations (HPR) (WHMIS 2015-GHS).

Hazard and Precautionary Statements

Lujob M Conveyor Lubricant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

Ingredient(s)	CAS #	Weight %	
Potassium tallate	61790-44-1	5 - 10%	
fatty acids, coco, potassium salts	61789-30-8	3 - 7%	
Tetrasodium salt of EDTA	64-02-8	1 - 5%	
Dipropylene glycol methyl ether	34590-94-8	1 - 5%	
Sodium alpha olefin sulfonate	68439-57-6	1 - 5%	
Alcohol ethoxylate	68002-97-1	> 0.1 - 1%	
Sodium hydroxide	1310-73-2	> 0.1 - 1%	

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

<u>Most Important Symptoms/Effects:</u> No information available. Immediate medical attention and special treatment needed Not applicable.

Diluted Product:

Eyes: Rinse with plenty of water.

Skin: No specific first aid measures are required Inhalation: No specific first aid measures are required Ingestion: IF SWALLOWED: Call a Poison Center (1-800-851-7145) or doctor/physician if you feel unwell.

5. FIRE-FIGHTING MEASURES

Specific methods: Suitable extinguishing media: Specific hazards: No special methods required The product is not flammable. Extinguish fire using agent suitable for surrounding fire. None known. Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. **Extinguishing media which must not be used for safety reasons:** No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Environmental precautions and clean-up methods: Put on appropriate personal protective equipment (see Section 8.). Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Mix only with water. DO NOT MIX WITH AMMONIA, BLEACH, OR OTHER CHLORINATED COMPOUNDS. May vigorously react with strong alkaline products resulting in spattering and excessive heat. Can react to release hazardous gases. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not taste or swallow. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Absorb spillage to prevent material damage. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Store in corrosive-resistant container with a resistant inner liner.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	ACGIH	OSHA
Dipropylene glycol methyl ether	50 ppm (TWA)	Skin
		100 ppm (TWA)
		600 mg/m ³ (TWA)
Sodium hydroxide	2 mg/m ³ (Ceiling)	2 mg/m ³ (TWA)

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

It is the responsibility of the employer to determine the potential risk of exposure to hazardous chemicals for employees in the workplace in order to determine the necessity, selection, and use of personal protective equipment.

Eye protection:	Chemical-splash goggles.
Hand protection:	Chemical-resistant gloves.
Skin and body protection:	No personal protective equipment required under normal use conditions.
Respiratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

Eye protection:No personal protective equipment required under normal use conditions.Hand protection:No personal protective equipment required under normal use conditions.Skin and body protection:No personal protective equipment required under normal use conditions.Respiratory protection:No personal protective equipment required under normal use conditions.Hygiene measures:Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid Evaporation Rate: No information available Odor threshold: No information available. Melting point/freezing point (°C): Not determined Autoignition temperature: No information available Solubility in other solvents: No information available Density: 1.042 Kg/L Bulk density: No information available Flash point (°F): > 200 °F > 93 °C Kinematic viscosity No information available VOC: 3.1 %* Flammability (Solid or Gas): Not applicable Sustained combustion: Not applicable Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear , Pearlescent , from Yellow to Green Odor: Surfactant Boiling point/range: Not determined Decomposition temperature: Not determined Solubility: Completely Soluble Relative Density (relative to water): 1.04 Vapor density: No information available Vapor pressure: No information available. Partition coefficient (n-octanol/water): No information available Elemental Phosphorus: 0.00 % by wt. pH: > 11 Corrosion to metals: Metal corrosive

Dilution pH: \approx 11 Dilution Flash Point (°F): > 200 °F > 93.4 °C VOC % by wt. at use dilution: 0.06 %

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Stability: Possibility of hazardous reactions: Hazardous decomposition products: Materials to avoid:

Not Applicable The product is stable May vigorously react with strong alkaline products resulting in spattering and excessive heat. None reasonably foreseeable. Ammonia. Do not mix with chlorinated products (such as bleach). Do not mix with any other product or chemical unless specified in the use directions. Conditions to avoid:

No information available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Causes skin irritation. Symptoms may include pain (which may be delayed), redness, and/or discomfort.
Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.
Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.
Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.
Sensitization: No known effects.
Target Organs (SE): None known

Target Organs (RE):

Numerical measures of toxicity

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Mobility: No information available.

Other adverse effects No other adverse effects known.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products (undiluted product): This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Waste from residues / unused products (diluted product): This product, when diluted as stated on this SDS, is not a hazardous waste according to Federal regulations (40 CFR 261). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

RCRA Hazard Class (undiluted product): D002 Corrosive Waste RCRA Hazard Class (diluted product): Not Regulated Contaminated Packaging: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: The information provided below is the full transportation classification for this product. This description does not account for the package size(s) of this product, that may fall under a quantity exception, according to the applicable transportation regulations. When shipping dangerous goods, please consult with your internal, certified hazardous materials specialist to determine if any exceptions can be applied to your shipment.

DOT (Ground) Bill of Lading Description: UN1760, CORROSIVE LIQUID, N.O.S., (tetrasodium salt of EDTA), 8, III

IMDG (Ocean) Bill of Lading Description: UN1760, CORROSIVE LIQUID, N.O.S., (tetrasodium salt of EDTA), 8, III

15. REGULATORY INFORMATION

International Inventories at CAS# Level

US RIGHT TO KNOW (RTK)

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313			
Dipropylene glycol methyl ether	34590-94-8	1 - 5%			Х			
Sodium hydroxide	1310-73-2	> 0.1 - 1%	1000					
Ingredient(s)	C	ΑΑ ΗΑΡ	CAA ODS	CWA Prio	CWA Priority Pollutants			
Dipropylene glycol methyl ethe	r	Х						

Canadian Regulations

16. OTHER INFORMATION

NFPA (National Fire Protection Association) Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3 Flammability 0 Instability 0 Special Hazards -

Diluted Product:

Health 0 Flammability 0 Instability 0 Special Hazards -

Revision: 2024-07-31 **Version:** 02.0

Reason for revision: Prepared by: Not applicable North American Regulatory Affairs

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.