

Taski Tapi Defoam C1g

Revision: 2024-08-08

Version: 04.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Taski Tapi Defoam C1g

UFI: 7A35-30C2-D00F-GW0R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use: Carpet / Upholstery cleaner.
Defoaming agent.
For professional use only.

Uses advised against: Uses other than those identified are not recommended.

SWED - Sector-specific worker exposure description :

AISE_SWED_PW_4_1
AISE_SWED_PW_11_1
AISE_SWED_PW_19_1

1.3 Details of the supplier of the safety data sheet

Diversey Europe Operations BV, De Corridor 4, 3621ZB Breukelen [Maarssebroeksedijk 2, 3542DN Utrecht], The Netherlands

Contact details

Diversey Ltd
Weston Favell Centre, Northampton NN3 8PD, United Kingdom
Tel: 01604 405311, Fax: 01604 406809
Regulatory Email: customerservice.uk@solenis.com

1.4 Emergency telephone number

Seek medical advice (show the label or safety data sheet where possible)
For medical or environmental emergency only:
call 0800 052 0185

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 2 (H225)
Specific target organ toxicity - Single exposure, Category 3 (H336)
Eye irritation, Category 2 (H319)

2.2 Label elements



Signal word: Danger.

Contains Propan-2-ol (Isopropyl Alcohol)

Hazard statements:

H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P403 + P235 - Store in a well-ventilated place. Keep cool.

2.3 Other hazards

No other hazards known.

Taski Tapi Defoam C1g

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Ingredient(s)	EC number	CAS number	REACH number	Classification	Notes	Weight percent
Propan-2-ol	200-661-7	67-63-0	01-211945755 8-25	Flammable liquids, Category 2 (H225) Specific target organ toxicity - Single exposure, Category 3 (H336) Eye irritation, Category 2 (H319)		>= 75

Workplace exposure limit(s), if available, are listed in subsection 8.1.

ATE, if available, are listed in section 11.

For the full text of the H and EUH phrases mentioned in this Section, see Section 16..

SECTION 4: First aid measures**4.1 Description of first aid measures**

Inhalation:	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE, doctor or physician if you feel unwell.
Skin contact:	Wash skin with plenty of lukewarm, gently flowing water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or attention.
Eye contact:	Hold eyelids apart and flush eyes with plenty of lukewarm water for at least 15 minutes. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention.
Ingestion:	Rinse mouth. Immediately drink 1 glass of water. Never give anything by mouth to an unconscious person. Get medical attention or advice if you feel unwell.
Self-protection of first aider:	Consider personal protective equipment as indicated in subsection 8.2.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation:	May cause drowsiness or dizziness.
Skin contact:	No known effects or symptoms in normal use.
Eye contact:	Causes severe irritation.
Ingestion:	No known effects or symptoms in normal use.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Carbon dioxide. Dry powder. Water spray jet. Fight larger fires with water spray jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No special hazards known.

5.3 Advice for firefighters

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Turn off all sources of ignition. Ventilate the area. Ensure adequate ventilation. Do not breathe dust or vapour.

6.2 Environmental precautions

Dilute with plenty of water. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dyke to collect large liquid spills. Absorb with liquid-binding material (sand, diatomite, universal binders). Do not place spilled materials back into the original container. Collect in closed and suitable containers for disposal.

6.4 Reference to other sections

For personal protective equipment see subsection 8.2. For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Measures to prevent fire and explosions:

Taski Tapi Defoam C1g

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools.

Measures required to protect the environment:

For environmental exposure controls see subsection 8.2.

Advices on general occupational hygiene:

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not mix with other products unless advised by Diversey. Wash hands before breaks and at the end of workday. Take off immediately all contaminated clothing. Store used personal protective equipment separately. Avoid contact with skin and eyes. Do not breathe vapours. Do not breathe spray. Use only outdoors or in a well-ventilated area. See chapter 8.2, Exposure controls / Personal protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local and national regulations. Store in a well-ventilated place. Store in a closed container. Keep only in original packaging. Keep cool. Keep away from heat and direct sunlight.

For conditions to avoid see subsection 10.4. For incompatible materials see subsection 10.5.

Comah - Lower Tier requirements (tonnes): 5000

Comah - Upper Tier requirements (tonnes): 50000

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Workplace exposure limits**

Air limit values, if available:

Ingredient(s)	UK - Long term value(s)	UK - Short term value(s)
Propan-2-ol	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³

Biological limit values, if available:

Recommended monitoring procedures, if available:

Additional exposure limits under the conditions of use, if available:

DNEL/DMEL and PNEC values**Human exposure**

DNEL/DMEL oral exposure - Consumer (mg/kg bw)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
Propan-2-ol	-	-	-	26

DNEL/DMEL dermal exposure - Worker

Ingredient(s)	Short term - Local effects	Short term - Systemic effects (mg/kg bw)	Long term - Local effects	Long term - Systemic effects (mg/kg bw)
Propan-2-ol	-	-	-	888

DNEL/DMEL dermal exposure - Consumer

Ingredient(s)	Short term - Local effects	Short term - Systemic effects (mg/kg bw)	Long term - Local effects	Long term - Systemic effects (mg/kg bw)
Propan-2-ol	-	-	-	319

DNEL/DMEL inhalatory exposure - Worker (mg/m³)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
Propan-2-ol	-	-	-	500

DNEL/DMEL inhalatory exposure - Consumer (mg/m³)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
Propan-2-ol	-	-	-	89

Environmental exposure

Environmental exposure - PNEC

Ingredient(s)	Surface water, fresh (mg/l)	Surface water, marine (mg/l)	Intermittent (mg/l)	Sewage treatment plant (mg/l)
Propan-2-ol	140.9	140.9	140.9	2251

Taski Tapi Defoam C1g

Environmental exposure - PNEC, continued

Ingredient(s)	Sediment, freshwater (mg/kg)	Sediment, marine (mg/kg)	Soil (mg/kg)	Air (mg/m ³)
Propan-2-ol	552	552	28	-

8.2 Exposure controls

The following information applies for the uses indicated in subsection 1.2 of the Safety Data Sheet. If available, please refer to the product information sheet for application and handling instructions. Normal use conditions are assumed for this section.

Recommended safety measures for handling the undiluted product:

Appropriate engineering controls: Provide a good standard of general ventilation.
Appropriate organisational controls: Avoid direct contact and/or splashes where possible. Train personnel. Users are advised to consider national Occupational Exposure Limits or other equivalent values, if available.

REACH use scenarios considered for the undiluted product:

	SWED - Sector-specific worker exposure description	LCS	PROC	Duration (min)	ERC
Spray application	AISE_SWED_PW_11_1	PW	PROC 11	60	ERC8a
Manual application	AISE_SWED_PW_19_1	PW	PROC 19	480	ERC8a
Automatic application in a dedicated system	AISE_SWED_PW_4_1	PW	PROC 4	480	ERC8a

Personal protective equipment

Eye / face protection: Safety glasses are not normally required. However, their use is recommended in those cases where splashes may occur when handling the product (EN 16321 / EN 166).
Hand protection: No special requirements under normal use conditions.
Body protection: No special requirements under normal use conditions.
Respiratory protection: Respiratory protection is not normally required. However, inhalation of vapour, spray, gas or aerosols should be avoided. Trigger spray bottle application: No special requirements under normal use conditions. Apply technical measures to comply with the occupational exposure limits, if available.

Environmental exposure controls: Should not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Information in this section refers to the product, unless it is specifically stated that substance data is listed

	Method / remark
Physical state: Liquid	
Colour: Clear , Colourless	
Odour: Product specific	
Odour threshold: Not applicable	
Melting point/freezing point (°C): Not determined	Not relevant to classification of this product
Initial boiling point and boiling range (°C): Not determined	See substance data

Substance data, boiling point

Ingredient(s)	Value (°C)	Method	Atmospheric pressure (hPa)
Propan-2-ol	82	Method not given	1013

	Method / remark
Flammability (solid, gas): Not applicable to liquids	
Flammability (liquid): Flammable.	
Flash point (°C): ≈ 15 °C	closed cup
Sustained combustion: The product sustains combustion (UN Manual of Tests and Criteria, section 32, L.2)	
Lower and upper explosion limit/flammability limit (%): Not determined	See substance data

Substance data, flammability or explosive limits, if available:

Ingredient(s)	Lower limit (% vol)	Upper limit (% vol)
Propan-2-ol	2	13

	Method / remark
Autoignition temperature: Not determined	

Taski Tapi Defoam C1g

Decomposition temperature: Not applicable.
pH: No information available.
Kinematic viscosity: Not determined
Solubility in / Miscibility with water: Fully miscible

Substance data, solubility in water

Ingredient(s)	Value (g/l)	Method	Temperature (°C)
Propan-2-ol	Soluble	Method not given	

Substance data, partition coefficient n-octanol/water (log Kow): see subsection 12.3

Vapour pressure: Not determined

Method / remark

See substance data

Substance data, vapour pressure

Ingredient(s)	Value (Pa)	Method	Temperature (°C)
Propan-2-ol	4200	Method not given	20

Relative density: ≈ 0.80 (20 °C)
Relative vapour density: No data available.
Particle characteristics: No data available.

Method / remark

OECD 109 (EU A.3)

Not relevant to classification of this product
 Not applicable to liquids.

9.2 Other information**9.2.1 Information with regard to physical hazard classes**

Explosive properties: Not explosive. Vapours may form explosive mixtures with air.

Oxidising properties: Not oxidising.

Corrosion to metals: Not corrosive

Weight of evidence

9.2.2 Other safety characteristics

No other relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal storage and use conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known under normal storage and use conditions.

10.4 Conditions to avoid

None known under normal storage and use conditions.

10.5 Incompatible materials

None known under normal use conditions.

10.6 Hazardous decomposition products

None known under normal storage and use conditions.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Mixture data: .

Relevant calculated ATE(s):

ATE - Oral (mg/kg): >2000

Substance data, where relevant and available, are listed below:.

Acute toxicity

Acute oral toxicity

Ingredient(s)	Endpoint	Value	Species	Method	Exposure	ATE Oral
---------------	----------	-------	---------	--------	----------	----------

Taski Tapi Defoam C1g

		(mg/kg)			time (h)	(mg/kg)
Propan-2-ol	LD ₅₀	5840	Rat	OECD 401 (EU B.1)		Not established

Acute dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)	ATE Dermal (mg/kg)
Propan-2-ol	LD ₅₀	> 2000	Rabbit	Method not given		Not established

Acute inhalative toxicity

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	LC ₅₀	> 25 (vapour)	Rat	OECD 403 (EU B.2)	6

Acute inhalative toxicity, continued

Ingredient(s)	ATE - inhalation, dust (mg/l)	ATE - inhalation, mist (mg/l)	ATE - inhalation, vapour (mg/l)	ATE - inhalation, gas (mg/l)
Propan-2-ol	Not established	Not established	Not established	Not established

Irritation and corrosivity

Skin irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	Not irritant	Rabbit	OECD 404 (EU B.4)	

Eye irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	Irritant	Rabbit	OECD 405 (EU B.5)	

Respiratory tract irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	No data available			

Sensitisation

Sensitisation by skin contact

Ingredient(s)	Result	Species	Method	Exposure time (h)
Propan-2-ol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / Buehler test	

Sensitisation by inhalation

Ingredient(s)	Result	Species	Method	Exposure time
Propan-2-ol	No data available			

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Mutagenicity

Ingredient(s)	Result (in-vitro)	Method (in-vitro)	Result (in-vivo)	Method (in-vivo)
Propan-2-ol	No evidence for mutagenicity, negative test results No evidence of genotoxicity, negative test results	OECD 471 (EU B.12/13)	No evidence of genotoxicity, negative test results	OECD 474 (EU B.12)

Carcinogenicity

Ingredient(s)	Effect
Propan-2-ol	No evidence for carcinogenicity, negative test results

Toxicity for reproduction

Ingredient(s)	Endpoint	Specific effect	Value (mg/kg bw/d)	Species	Method	Exposure time	Remarks and other effects reported
Propan-2-ol			No data available				

Repeated dose toxicity

Sub-acute or sub-chronic oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
Propan-2-ol		No data available				

Sub-chronic dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected

Taski Tapi Defoam C1g

Propan-2-ol		No data available				
-------------	--	-------------------	--	--	--	--

Sub-chronic inhalation toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
Propan-2-ol		No data available				

Chronic toxicity

Ingredient(s)	Exposure route	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time	Specific effects and organs affected	Remark
Propan-2-ol			No data available					

STOT-single exposure

Ingredient(s)	Affected organ(s)
Propan-2-ol	Central nervous system

STOT-repeated exposure

Ingredient(s)	Affected organ(s)
Propan-2-ol	No data available

Aspiration hazard

Substances with an aspiration hazard (H304), if any, are listed in section 3.

Potential adverse health effects and symptoms

Effects and symptoms related to the product, if any, are listed in subsection 4.2.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Endocrine disrupting properties - Human data, if available:

11.2.2 Other information

No other relevant information available.

SECTION 12: Ecological information

12.1 Toxicity

No data is available on the mixture.

Substance data, where relevant and available, are listed below:

Aquatic short-term toxicity

Aquatic short-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	LC ₅₀	> 100	<i>Pimephales promelas</i>	Method not given	48

Aquatic short-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	EC ₅₀	> 100	<i>Daphnia magna</i> Straus	Method not given	48

Aquatic short-term toxicity - algae

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
Propan-2-ol	EC ₅₀	> 100	<i>Scenedesmus quadricauda</i>	Method not given	72

Aquatic short-term toxicity - marine species

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (days)
Propan-2-ol		No data available			

Impact on sewage plants - toxicity to bacteria

Taski Tapi Defoam C1g

Ingredient(s)	Endpoint	Value (mg/l)	Inoculum	Method	Exposure time
Propan-2-ol	EC ₅₀	> 1000	Activated sludge	Method not given	

Aquatic long-term toxicity

Aquatic long-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
Propan-2-ol		No data available				

Aquatic long-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
Propan-2-ol		No data available				

Aquatic toxicity to other aquatic benthic organisms, including sediment-dwelling organisms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw sediment)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity

Terrestrial toxicity - soil invertebrates, including earthworms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - plants, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - birds, if available:

Ingredient(s)	Endpoint	Value	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - beneficial insects, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

Terrestrial toxicity - soil bacteria, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
Propan-2-ol		No data available				

12.2 Persistence and degradability**Abiotic degradation**

Abiotic degradation - photodegradation in air, if available:

Ingredient(s)	Half-life time	Method	Evaluation	Remark
Propan-2-ol	No data available			

Abiotic degradation - hydrolysis, if available:

Ingredient(s)	Half-life time in fresh water	Method	Evaluation	Remark
Propan-2-ol	No data available			

Abiotic degradation - other processes, if available:

Ingredient(s)	Type	Half-life time	Method	Evaluation	Remark
---------------	------	----------------	--------	------------	--------

Taski Tapi Defoam C1g

Propan-2-ol		No data available			
-------------	--	-------------------	--	--	--

Biodegradation

Ready biodegradability - aerobic conditions

Ingredient(s)	Inoculum	Analytical method	DT ₅₀	Method	Evaluation
Propan-2-ol			95 % in 21 day(s)	OECD 301E	Readily biodegradable

Ready biodegradability - anaerobic and marine conditions, if available:

Ingredient(s)	Medium & Type	Analytical method	DT ₅₀	Method	Evaluation
Propan-2-ol					No data available

Degradation in relevant environmental compartments, if available:

Ingredient(s)	Medium & Type	Analytical method	DT ₅₀	Method	Evaluation
Propan-2-ol					No data available

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ingredient(s)	Value	Method	Evaluation	Remark
Propan-2-ol	0.05	OECD 107	No bioaccumulation expected	

Bioconcentration factor (BCF)

Ingredient(s)	Value	Species	Method	Evaluation	Remark
Propan-2-ol	No data available				

12.4 Mobility in soil

Adsorption/Desorption to soil or sediment

Ingredient(s)	Adsorption coefficient Log K _{oc}	Desorption coefficient Log K _{oc} (des)	Method	Soil/sediment type	Evaluation
Propan-2-ol	No data available				Potential for mobility in soil, soluble in water

12.5 Results of PBT and vPvB assessment

Substances that fulfill the criteria for PBT/vPvB, if any, are listed in section 3.

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Environmental effects, if available:

12.7 Other adverse effects

No other adverse effects known.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Waste from residues / unused products:**

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. The cleaned packaging material is suitable for energy recovery or recycling in line with local legislation.

European Waste Catalogue:

16 03 05* - organic wastes containing dangerous substances.

Empty packaging**Recommendation:**

Dispose of observing national or local regulations.

Suitable cleaning agents:

Water, if necessary with cleaning agent.

SECTION 14: Transport information**Land transport (ADR/RID), Sea transport (IMDG), Air transport (ICAO-TI / IATA-DGR)****14.1 UN number or ID number:** 1219**14.2 UN proper shipping name:**

Taski Tapi Defoam C1g

Isopropanol (isopropyl alcohol) , solution

14.3 Transport hazard class(es):

Transport hazard class (and subsidiary risks): 3

14.4 Packing group: II**14.5 Environmental hazards:**

Environmentally hazardous: No

Marine pollutant: No

14.6 Special precautions for user: None known.**14.7 Maritime transport in bulk according to IMO instruments:** The product is not transported in bulk tankers.**Other relevant information:****ADR**

Classification code: F1

Tunnel restriction code: (D/E)

Hazard identification number: 33

IMO/IMDG

EmS: F-E, S-D

The product has been classified, labelled and packaged in accordance with the requirements of ADR and the provisions of the IMDG Code. Transport regulations include special provisions for certain classes of dangerous goods packed in limited quantities.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations :**

- Regulation (EC) 1907/2006 - REACH (UK amended)
- Regulation (EC) 1272/2008 - CLP (UK amended)
- Regulation (EC) 648/2004 - Detergents regulation (UK amended)
- Delegated Regulation (EU) 2017/2100 and Regulation (EU) 2018/605 (UK amended)
- Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)
- International Maritime Dangerous Goods (IMDG) Code

Authorisations or restrictions (Regulation (EC) No 1907/2006, Title VII respectively Title VIII): Not applicable.

Ingredients according to Detergents Regulation

Not applicable

Comah - classification: P5c - FLAMMABLE LIQUIDS

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out on the mixture

SECTION 16: Other information

The information in this document is based on our best present knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally binding contract

SDS code: MSDS4746

Version: 04.2

Revision: 2024-08-08

Reason for revision:

This data sheet contains changes from the previous version in section(s): 4, 6, 7, 8, 16, Overall design adjusted in accordance with Amendment 2020/878, Annex II of Regulation (EC) No 1907/2006

Classification procedure

The classification of the mixture is in general based on calculation methods using substance data, as required by Regulation (EC) No 1272/2008. If for certain classifications data on the mixture is available or for example bridging principles or weight of evidence can be used for classification, this will be indicated in the relevant sections of the Safety Data Sheet. See section 9 for physical chemical properties, section 11 for toxicological information and section 12 for ecological information.

Abbreviations and acronyms:

- AISE - The international Association for Soaps, Detergents and Maintenance Products
- ATE - Acute Toxicity Estimate
- DNEL - Derived No Effect Limit
- EC50 - effective concentration, 50%
- ERC - Environmental release categories
- EUH - CLP Specific hazard statement
- LC50 - Lethal Concentration, 50% / Median Lethal Concentration
- LCS - Life cycle stage

Taski Tapi Defoam C1g

- LD50 - Lethal Dose, 50% / Median Lethal dose
- NOAEL - No observed adverse effect level
- NOEL - No observed effect level
- OECD - Organisation for Economic Cooperation and Development
- PBT - Persistent, Bioaccumulative and Toxic
- PNEC - Predicted No Effect Concentration
- PROC - Process categories
- REACH number - REACH registration number, without supplier specific part
- vPvB - very Persistent and very Bioaccumulative
- H225 - Highly flammable liquid and vapour.
- H319 - Causes serious eye irritation.
- H336 - May cause drowsiness or dizziness.

End of Safety Data Sheet